

CSI Compatible Data Collector Cables

CSI 2110, 2115, 2120



Data Collector Cables - DB25 and 2 Socket MIL Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C3-006-D2C	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-C3-010-D2C	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-C3-016-D2C	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB108-C3-006-D2C	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-C3-010-D2C	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-C3-016-D2C	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB103-C3-004-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	4 ft (1,22 m)	Polyurethane	250°F (121°C)
CB103-C3-006-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C3-010-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB103-C3-(XXX)-D2C	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

Data Collector Cables - DB25 and BNC Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C3-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C3-006-F	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C3-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

CSI Compatible Data Collector Cables

CSI 2130



Data Collector Cables - 5 Pin Turck and 2 Socket MIL Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C76-006-D2C	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-C76-010-D2C	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-C76-016-D2C	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB108-C76-006-D2C	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-C76-010-D2C	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-C76-016-D2C	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB103-C76-004-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	4 ft (1,22 m)	Polyurethane	250°F (121°C)
CB103-C76-006-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C76-010-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB103-C76-(XXX)-D2C	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

Data Collector Cables - 5 Pin Turck and BNC Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C76-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C76-006-F	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C76-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)