

Diagnostic Instruments Compatible Data Collector Cables

DI-225-D



Data Collector Cables - 6 Pin Fischer and 2 Socket MIL Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C66-006-D2C	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-C66-010-D2C	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-C66-016-D2C	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB108-C66-006-D2C	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-C66-010-D2C	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-C66-016-D2C	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB103-C66-004-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	4 ft (1,22 m)	Polyurethane	250°F (121°C)
CB103-C66-006-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C66-010-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB103-C66-(XXX)-D2C	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

Data Collector Cables - 6 Pin Fischer and BNC Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C66-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C66-006-F	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C66-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

DLI Compatible Data Collector Cables

DLI DCA-31 For Single Sensor Input

(See pages CB-8.A and CB-9.A for triaxial applications)



Data Collector Cables - 6 Pin Fischer and 2 Socket MIL Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C66-006-D2C	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-C66-010-D2C	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-C66-016-D2C	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB108-C66-006-D2C	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-C66-010-D2C	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-C66-016-D2C	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB103-C66-004-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	4 ft (1,22 m)	Polyurethane	250°F (121°C)
CB103-C66-006-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C66-010-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB103-C66-(XXX)-D2C	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

Data Collector Cables - 6 Pin Fischer and BNC Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C66-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C66-006-F	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C66-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)



VIBRATION ANALYSIS HARDWARE