

DLI Data Collector Cables

Watchman® DCA-31™

Adapter Cables - 6 Pin Fischer (C325) and 4 Socket AMP Connector for Triaxial Acceleration Input



CB105-C325-001-C342	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket AMP connector, 1 ft. (.30 m) straight cable
CB105-C325-006-C342	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket AMP connector, 6 ft. (1.83 m) straight cable
CB117-C325-006-C342	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket AMP connector, 6 ft. (1.83 m) coiled cable
CB117-C325-010-C342	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket AMP connector, 10 ft. (3.05 m) coiled cable

Extension Cables - 4 Pin AMP (C343) and 4 Socket AMP (C342) Connector for Triaxial Acceleration Input



CB105-C342-004-C343	Black Polyurethane, 4 conductor cable, with 4 pin AMP and 4 socket AMP connector, 4 ft. (1.22 m) straight cable
CB105-C342-006-C343	Black Polyurethane, 4 conductor cable, with 4 pin AMP and 4 socket AMP connector, 6 ft. (1.83 m) straight cable
CB105-C342-010-C343	Black Polyurethane, 4 conductor cable, with 4 pin AMP and 4 socket AMP connector, 10 ft. (3.05 m) straight cable
CB117-C342-006-C343	Black Polyurethane, 4 conductor cable, with 4 pin AMP and 4 socket AMP connector, 6 ft. (1.22 m) coiled cable
CB117-C342-010-C343	Black Polyurethane, 4 conductor cable, with 4 pin AMP and 4 socket AMP connector, 10 ft. (1.83 m) coiled cable
CB117-C342-016-C343	Black Polyurethane, 4 conductor cable, with 4 pin AMP and 4 socket AMP connector, 16 ft. (4.88 m) coiled cable

Cables - 6 Pin Fischer (C325) and 4 socket mini MIL (J4C) Connector for Acceleration Input



For use with CTC AC115-1A and AC230-1A Triaxial Sensors

CB105-C325-004-J4C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket mini MIL connector, 4 ft. (1.22 m) straight cable
CB105-C325-006-J4C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket mini MIL connector, 6 ft. (1.83 m) straight cable
CB105-C325-010-J4C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket mini MIL connector, 10 ft. (3.05 m) straight cable
CB117-C325-006-J4C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket mini MIL connector, 6 ft. (1.83 m) coiled cable
CB117-C325-010-J4C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket mini MIL connector, 10 ft. (3.05 m) coiled cable
CB117-C325-016-J4C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 4 socket mini MIL connector, 16 ft. (4.88 m) coiled cable

Cables - 6 Pin Fischer (C325) and 2 socket MIL (D2C) Connector for Single Axis Point Acceleration Input



CB103-C66-004-D2C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 2 socket MIL connector, 4 ft. (1.22 m) straight cable
CB103-C66-006-D2C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 2 socket MIL connector, 6 ft. (1.83 m) straight cable
CB103-C66-010-D2C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 2 socket MIL connector, 10 ft. (3.05 m) straight cable
CB104-C66-006-D2C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 2 socket MIL connector, 6 ft. (1.83 m) coiled cable
CB104-C66-010-D2C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 2 socket MIL connector, 10 ft. (3.05 m) coiled cable
CB104-C66-016-D2C	Black Polyurethane, 4 conductor cable, with 6 pin Fischer and 2 socket MIL connector, 16 ft. (4.88 m) coiled cable



VIBRATION ANALYSIS HARDWARE