

# ENTEK / IRD Compatible Data Collector Cables

## ENTEK / IRD dataline®



### Data Collector Cables - 7 Pin and 2 Socket MIL Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C1-006-D2C	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-C1-010-D2C	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-C1-016-D2C	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB108-C1-006-D2C	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-C1-010-D2C	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-C1-016-D2C	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB103-C1-004-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	4 ft (1,22 m)	Polyurethane	250°F (121°C)
CB103-C1-006-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C1-010-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB103-C1-(XXX)-D2C	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

### Data Collector Cables - 7 Pin and BNC Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C1-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C1-006-F	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C1-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

# ENTEK / IRD Compatible Data Collector Cables

## ENTEK / IRD dataPAC® & enpac™



### Data Collector Cables - 7 Pin LEMO and 2 Socket MIL Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C22-006-D2C	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-C22-010-D2C	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-C22-016-D2C	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB108-C22-006-D2C	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-C22-010-D2C	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-C22-016-D2C	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)
CB103-C22-004-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	4 ft (1,22 m)	Polyurethane	250°F (121°C)
CB103-C22-006-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C22-010-D2C	Straight-General Purpose	.250 in (6,35 mm)	n/a	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB103-C22-(XXX)-D2C	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)

### Data Collector Cables - 7 Pin LEMO and BNC Connectors for Acceleration Input

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-C22-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C22-006-F	Straight-General Purpose	.250 in (6,35 mm)	n/a	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB103-C22-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	n/a	(XXX)=Length in ft.	Polyurethane	250°F (121°C)