

Portable Measurement Cables

2 Socket MIL to BNC



Straight Cables - 2 Socket MIL to BNC

Part Number	Cable Type	Cable Diameter	Cable Length	Cable Description	Cable Jacket	Maximum Temperature
CB103-D2C-004-F	Straight-General Purpose	.250 in (6,35 mm)	4 ft (1,22 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-D2C-006-F	Straight-General Purpose	.250 in (6,35 mm)	6 ft (1,83 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-D2C-010-F	Straight-General Purpose	.250 in (6,35 mm)	10 ft (3,05 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-D2C-025-F	Straight-General Purpose	.250 in (6,35 mm)	25 ft (7,62 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-F-050-F	Straight-General Purpose	.250 in (6,35 mm)	50 ft (15,24)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-D2C-XXX-F	Straight-(Custom Length)	.250 in (6,35 mm)	XXX = Length in ft.	Twisted/Shielded	Polyurethane	250°F (121°C)

Coiled Cables - General Purpose - 2 Socket MIL to BNC

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-D2C-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-D2C-010-F	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-D2C-016-F	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)

Coiled Cables - Light Weight - 2 Socket MIL to BNC

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB108-D2C-006-F	Coiled-General Purpose	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-D2C-010-F	Coiled-General Purpose	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-D2C-016-F	Coiled-General Purpose	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)

BNC Cables - Straight & Coiled

BNC to BNC



Straight Cables - General Purpose - BNC to BNC

Part Number	Cable Type	Cable Diameter	Cable Length	Cable Description	Cable Jacket	Maximum Temperature
CB103-F-004-F	Straight-General Purpose	.250 in (6,35 mm)	4 ft (1,22 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-F-006-F	Straight-General Purpose	.250 in (6,35 mm)	6 ft (1,83 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-F-010-F	Straight-General Purpose	.250 in (6,35 mm)	10 ft (3,05 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-F-025-F	Straight-General Purpose	.250 in (6,35 mm)	25 ft (7,62 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-F-050-F	Straight-General Purpose	.250 in (6,35 mm)	50 ft (15,24)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB103-F-(XXX)-F	Straight-(Custom Length)	.250 in (6,35 mm)	(XXX) =Length in ft.	Twisted/Shielded	Polyurethane	250°F (121°C)

Straight Cables - Light Weight - BNC to BNC

Part Number	Cable Type	Cable Diameter	Cable Length	Cable Description	Cable Jacket	Maximum Temperature
CB110-F-004-F	Straight-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB110-F-006-F	Straight-Lightweight	.175 in (4,45 mm)	6 ft (1,83 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB110-F-010-F	Straight-Lightweight	.175 in (4,45 mm)	10 ft (3,05 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB110-F-025-F	Straight-Lightweight	.175 in (4,45 mm)	25 ft (7,62 m)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB110-F-050-F	Straight-Lightweight	.175 in (4,45 mm)	50 ft (15,24)	Twisted/Shielded	Polyurethane	250°F (121°C)
CB110-F-(XXX)-F	Straight-(Custom Length)	.175 in (4,45 mm)	(XXX) =Length in ft.	Twisted/Shielded	Polyurethane	250°F (121°C)

Coiled Cables - General Purpose - BNC to BNC

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB104-F-006-F	Coiled-General Purpose	.210 in (5,33 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB104-F-010-F	Coiled-General Purpose	.210 in (5,33 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB104-F-016-F	Coiled-General Purpose	.210 in (5,33 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)

Coiled Cables - Light Weight - BNC to BNC

Part Number	Cable Type	Cable Diameter	Retracted Length	Extended Length (Max)	Cable Jacket	Maximum Temperature
CB108-F-006-F	Coiled-Lightweight	.175 in (4,45 mm)	2 ft (0,61 m)	6 ft (1,83 m)	Polyurethane	250°F (121°C)
CB108-F-010-F	Coiled-Lightweight	.175 in (4,45 mm)	3 ft (0,91 m)	10 ft (3,05 m)	Polyurethane	250°F (121°C)
CB108-F-016-F	Coiled-Lightweight	.175 in (4,45 mm)	4 ft (1,22 m)	16 ft (4,88 m)	Polyurethane	250°F (121°C)

