

Standard Cables - For Permanent Monitoring

CB102-A2A-006-Z
CB102-A2A-010-Z
 CB102-A2A-015-Z
CB102-A2A-020-Z
 CB102-A2A-025-Z
CB102-A2A-030-Z
 CB102-A2A-040-Z
CB102-A2A-050-Z
CB102-A2A-075-Z
CB102-A2A-100-Z



A2A **CB102**
 2 Socket
 "MIL E QUAL"
 Connector
 250° F (121° C)
 Red Teflon™ jacketed
 cable, twisted,
 shielded pair
 (Blunt Cut)
 400° F (204° C)

CB102-A2E-006-Z
CB102-A2E-010-Z
 CB102-A2E-015-Z
CB102-A2E-020-Z
 CB102-A2E-025-Z
CB102-A2E-030-Z
 CB102-A2E-040-Z
CB102-A2E-050-Z
CB102-A2E-075-Z
CB102-A2E-100-Z



A2E **CB102**
 2 Socket Right
 Angle "MIL E
 QUAL" Connector
 250° F (121° C)
 Red Teflon™ jacketed
 cable, twisted,
 shielded pair
 (Blunt Cut)
 400° F (204° C)

CB102-B2A-006-Z
CB102-B2A-010-Z
 CB102-B2A-015-Z
CB102-B2A-020-Z
 CB102-B2A-025-Z
CB102-B2A-030-Z
 CB102-B2A-040-Z
CB102-B2A-050-Z
CB102-B2A-075-Z
CB102-B2A-100-Z



B2A **CB102**
 2 Socket
 Seal Tight Boot
 Connector
 250° F (121° C)
 Red Teflon™ jacketed
 cable, twisted,
 shielded pair
 (Blunt Cut)
 400° F (204° C)

CB102-J2A-006-Z
 CB102-J2A-010-Z
 CB102-J2A-015-Z
 CB102-J2A-020-Z
 CB102-J2A-025-Z
CB102-J2A-030-Z
 CB102-J2A-040-Z
 CB102-J2A-050-Z
 CB102-J2A-075-Z
 CB102-J2A-100-Z



J2A **CB102**
 2 Socket
 "mini MIL"
 Connector
 250° F (121° C)
 (permanent
 measurements)
 Red Teflon™ jacketed
 cable, twisted,
 shielded pair
 (Blunt Cut)
 400° F (204° C)

CB103-A2A-006-Z
CB103-A2A-010-Z
 CB103-A2A-015-Z
CB103-A2A-020-Z
 CB103-A2A-025-Z
CB103-A2A-030-Z
 CB103-A2A-040-Z
CB103-A2A-050-Z
CB103-A2A-075-Z
CB103-A2A-100-Z



A2A **CB103**
 2 Socket
 "MIL E QUAL"
 Connector
 250° F (121° C)
 Black polyurethane
 jacketed cable,
 twisted, shielded
 pair (Blunt Cut)
 250° F (121° C)

CB103-A2E-006-Z
CB103-A2E-010-Z
 CB103-A2E-015-Z
CB103-A2E-020-Z
 CB103-A2E-025-Z
CB103-A2E-030-Z
 CB103-A2E-040-Z
CB103-A2E-050-Z
CB103-A2E-075-Z
CB103-A2E-100-Z



A2E **CB103**
 2 Socket Right
 Angle "MIL E
 QUAL" Connector
 250° F (121° C)
 Black polyurethane
 jacketed cable,
 twisted, shielded
 pair (Blunt Cut)
 250° F (121° C)

CB103-B2A-006-Z
CB103-B2A-010-Z
 CB103-B2A-015-Z
CB103-B2A-020-Z
 CB103-B2A-025-Z
CB103-B2A-030-Z
 CB103-B2A-040-Z
CB103-B2A-050-Z
CB103-B2A-075-Z
CB103-B2A-100-Z



B2A **CB103**
 2 Socket
 Seal Tight Boot
 Connector
 250° F (121° C)
 Black polyurethane
 jacketed cable,
 twisted, shielded
 pair (Blunt Cut)
 250° F (121° C)

CB105-J4A-006-Z
 CB105-J4A-010-Z
 CB105-J4A-015-Z
 CB105-J4A-020-Z
 CB105-J4A-025-Z
CB105-J4A-030-Z
 CB105-J4A-040-Z
 CB105-J4A-050-Z
 CB105-J4A-075-Z
 CB105-J4A-100-Z



J4A **CB105**
 4 Socket
 "mini MIL"
 Connector
 250° F (121° C)
 (permanent
 measurements)
 Black polyurethane
 jacketed cable,
 4 conductor, twisted,
 shielded pair
 (Blunt Cut)
 250° F (121° C)

CB105-J4C-006-Z
 CB105-J4C-010-Z
 CB105-J4C-015-Z
 CB105-J4C-020-Z
 CB105-J4C-025-Z
CB105-J4C-030-Z
 CB105-J4C-040-Z
 CB105-J4C-050-Z
 CB105-J4C-075-Z
 CB105-J4C-100-Z



J4C **CB105**
 4 Socket
 "mini MIL"
 Connector
 250° F (121° C)
 (portable
 measurements)
 Black polyurethane
 jacketed cable,
 4 conductor, twisted,
 shielded pair
 (Blunt Cut)
 250° F (121° C)

CB110-J2A-006-Z
 CB110-J2A-010-Z
 CB110-J2A-015-Z
 CB110-J2A-020-Z
 CB110-J2A-025-Z
CB110-J2A-030-Z
 CB110-J2A-040-Z
 CB110-J2A-050-Z
 CB110-J2A-075-Z
 CB110-J2A-100-Z



J2A **CB110**
 2 Socket
 "mini MIL"
 Connector
 250° F (121° C)
 (permanent
 measurements)
 Light weight, black
 polyurethane cable,
 armor jacketed
 (Blunt Cut)
 400° F (204° C)

Note: Bold face items feature a discounted pricing structure.



VIBRATION ANALYSIS HARDWARE