




Standard Cables - For Permanent Monitoring

| | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>CB110-J2C-006-Z CB110-J2C-010-Z CB110-J2C-015-Z CB110-J2C-020-Z CB110-J2C-025-Z CB110-J2C-030-Z CB110-J2C-040-Z CB110-J2C-050-Z CB110-J2C-075-Z CB110-J2C-100-Z</p>   <p>J2C 2 Socket "mini MIL" Connector 250° F (121° C) (portable measurements)</p> <p>CB110 Light weight, black polyurethane cable, armor jacketed (Blunt Cut) 400° F (204° C)</p> | <p>CB111-A2A-006-Z CB111-A2A-010-Z CB111-A2A-015-Z CB111-A2A-020-Z CB111-A2A-025-Z CB111-A2A-030-Z CB111-A2A-040-Z CB111-A2A-050-Z CB111-A2A-075-Z CB111-A2A-100-Z</p>   <p>A2A 2 Socket "MIL E QUAL" Connector 250° F (121° C)</p> <p>CB111 Yellow Teflon™ jacketed cable twisted, shielded pair (Blunt Cut) 400° F (204° C)</p> |
| <p>CB111-A2E-006-Z CB111-A2E-010-Z CB111-A2E-015-Z CB111-A2E-020-Z CB111-A2E-025-Z CB111-A2E-030-Z CB111-A2E-040-Z CB111-A2E-050-Z CB111-A2E-075-Z CB111-A2E-100-Z</p>   <p>A2E 2 Socket Right Angle "MIL E QUAL" Connector 250° F (121° C)</p> <p>CB111 Yellow Teflon™ jacketed, cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)</p> | <p>CB111-B2A-006-Z CB111-B2A-010-Z CB111-B2A-015-Z CB111-B2A-020-Z CB111-B2A-025-Z CB111-B2A-030-Z CB111-B2A-040-Z CB111-B2A-050-Z CB111-B2A-075-Z CB111-B2A-100-Z</p>   <p>B2A 2 Socket Seal Tight Boot Connector 250° F (121° C)</p> <p>CB111 Yellow Teflon™ jacketed cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)</p> |
| <p>CB111-J2A-006-Z CB111-J2A-010-Z CB111-J2A-015-Z CB111-J2A-020-Z CB111-J2A-025-Z CB111-J2A-030-Z CB111-J2A-040-Z CB111-J2A-050-Z CB111-J2A-075-Z CB111-J2A-100-Z</p>   <p>J2A 2 Socket "mini MIL" Connector 250° F (121° C) (permanent measurements)</p> <p>CB111 Yellow Teflon™ jacketed cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)</p> | <p>CB112-A3A-006-Z CB112-A3A-010-Z CB112-A3A-015-Z CB112-A3A-020-Z CB112-A3A-025-Z CB112-A3A-030-Z CB112-A3A-040-Z CB112-A3A-050-Z CB112-A3A-075-Z CB112-A3A-100-Z</p>   <p>A3A 3 Socket "MIL E QUAL" Connector 250° F (121° C)</p> <p>CB112 White Teflon™ jacketed cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)</p> |
| <p>CB112-B3A-006-Z CB112-B3A-010-Z CB112-B3A-015-Z CB112-B3A-020-Z CB112-B3A-025-Z CB112-B3A-030-Z CB112-B3A-040-Z CB112-B3A-050-Z CB112-B3A-075-Z CB112-B3A-100-Z</p>   <p>B3A 3 Socket Seal Tight Boot Connector 250° F (121° C)</p> <p>CB112 White Teflon™ jacketed cable, 3 conductor, shielded (Blunt Cut) 400° F (204° C)</p> | <p>CB206-A2A-006-Z CB206-A2A-010-Z CB206-A2A-015-Z CB206-A2A-020-Z CB206-A2A-025-Z CB206-A2A-030-Z CB206-A2A-040-Z CB206-A2A-050-Z CB206-A2A-075-Z CB206-A2A-100-Z</p>   <p>A2A 2 Socket "MIL E QUAL" Connector 250° F (121° C)</p> <p>CB206 Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)</p> |
| <p>CB206-A2E-006-Z CB206-A2E-010-Z CB206-A2E-015-Z CB206-A2E-020-Z CB206-A2E-025-Z CB206-A2E-030-Z CB206-A2E-040-Z CB206-A2E-050-Z CB206-A2E-075-Z CB206-A2E-100-Z</p>   <p>A2E 2 Socket Right Angle "MIL E QUAL" Connector 250° F (121° C)</p> <p>CB206 Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)</p> | <p>CB206-B2A-006-Z CB206-B2A-010-Z CB206-B2A-015-Z CB206-B2A-020-Z CB206-B2A-025-Z CB206-B2A-030-Z CB206-B2A-040-Z CB206-B2A-050-Z CB206-B2A-075-Z CB206-B2A-100-Z</p>   <p>B2A 2 Socket Seal Tight Boot Connector 250° F (121° C)</p> <p>CB206 Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)</p> |

Note: Bold face items feature a discounted pricing structure.