





Standard Cables - For Permanent Monitoring

CB206-J2A-006-Z CB206-J2A-010-Z CB206-J2A-015-Z CB206-J2A-020-Z CB206-J2A-025-Z CB206-J2A-030-Z CB206-J2A-040-Z CB206-J2A-050-Z CB206-J2A-075-Z CB206-J2A-100-Z	 	<p>J2A</p> 2 Socket "mini MIL" Connector 250° F (121° C) (permanent measurements)	<p>CB206</p> Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)	CB218-J4A-006-Z CB218-J4A-010-Z CB218-J4A-015-Z CB218-J4A-020-Z CB218-J4A-025-Z CB218-J4A-030-Z CB218-J4A-040-Z CB218-J4A-050-Z CB218-J4A-075-Z CB218-J4A-100-Z	 	<p>J4A</p> 4 Socket "mini MIL" Connector 250° F (121° C) (permanent measurements)	<p>CB218</p> Twisted, shielded pair cable, w/ drain wire, 4 conductor, armor jacketed cable (Blunt Cut) 400° F (204° C)
--	---	---	---	--	---	---	---

High Temperature Cables

CB111-A2B-006-Z CB111-A2B-010-Z CB111-A2B-015-Z CB111-A2B-020-Z CB111-A2B-025-Z CB111-A2B-030-Z CB111-A2B-040-Z CB111-A2B-050-Z CB111-A2B-075-Z CB111-A2B-100-Z	 	<p>HIGH TEMP</p> <p>A2B</p> 2 Socket "MIL E QUAL" Connector 350° F (177° C)	<p>CB102</p> Red Teflon™ jacketed cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)	CB102-A2F-006-Z CB102-A2F-010-Z CB102-A2F-015-Z CB102-A2F-020-Z CB102-A2F-025-Z CB102-A2F-030-Z CB102-A2F-040-Z CB102-A2F-050-Z CB102-A2F-075-Z CB102-A2F-100-Z	 	<p>HIGH TEMP</p> <p>A2F</p> 2 Socket Right Angle "MIL E QUAL" Connector 350° F (177° C)	<p>CB102</p> Red Teflon™ jacketed cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)
CB102-B2B-006-Z CB102-B2B-010-Z CB102-B2B-015-Z CB102-B2B-020-Z CB102-B2B-025-Z CB102-B2B-030-Z CB102-B2B-040-Z CB102-B2B-050-Z CB102-B2B-075-Z CB102-B2B-100-Z	 	<p>HIGH TEMP</p> <p>B2B</p> 2 Socket Seal Tight Boot Connector, 350° F (177° C)	<p>CB102</p> Red Teflon™ jacketed cable, twisted, shielded pair (Blunt Cut) 400° F (204° C)	CB206-A2B-006-Z CB206-A2B-010-Z CB206-A2B-015-Z CB206-A2B-020-Z CB206-A2B-025-Z CB206-A2B-030-Z CB206-A2B-040-Z CB206-A2B-050-Z CB206-A2B-075-Z CB206-A2B-100-Z	 	<p>HIGH TEMP</p> <p>A2B</p> 2 Socket "MIL E QUAL" Connector 350° F (177° C)	<p>CB206</p> Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)
CB206-A2F-006-Z CB206-A2F-010-Z CB206-A2F-015-Z CB206-A2F-020-Z CB206-A2F-025-Z CB206-A2F-030-Z CB206-A2F-040-Z CB206-A2F-050-Z CB206-A2F-075-Z CB206-A2F-100-Z	 	<p>HIGH TEMP</p> <p>A2F</p> 2 Socket Right Angle "MIL E QUAL" Connector 350° F (177° C)	<p>CB206</p> Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)	CB206-B2B-006-Z CB206-B2B-010-Z CB206-B2B-015-Z CB206-B2B-020-Z CB206-B2B-025-Z CB206-B2B-030-Z CB206-B2B-040-Z CB206-B2B-050-Z CB206-B2B-075-Z CB206-B2B-100-Z	 	<p>HIGH TEMP</p> <p>B2B</p> 2 Socket Seal Tight Boot Connector, 350° F (177° C)	<p>CB206</p> Twisted, shielded pair cable, w/ drain wire, armor jacketed (Blunt Cut) 400° F (204° C)

