

Specifications

Electrical

| | |
|--------|---|
| Inputs | Terminal Block 2 Inputs per Channel (+,-) |
| Output | BNC Jack Per Channel Electrically Isolated |

Enclosure

| | |
|--|----------------|
| Rating | NEMA 4X (IP65) |
| Door Attachment | 4 Screws |
| Material | Polycarbonate |
| Screw Torque for Door & Mounting Feet | 40-45 in-oz |

Environmental

| | |
|--------------------|----------------------------------|
| Temperature Rating | -50° to 180° F (-58° to 82° C) |
| Resistance | Resistant to Hose Directed Fluid |

Features

- **Cost Effective**
- **Connects remotely installed accelerometers to portable data collectors**
- **Water Resistant enclosure and protective BNC cap covers**
- **1, 2, 3 and 4 channel versions**
- **Optional cord grip inputs provide quick and secure cable entry into enclosure (See Model CT101-4C Photo)**



Model CT101-4A (as shown)



Model CT101-4C
(as shown)

Ordering Information

| Part Number | Channels | Factory Installed Cable Entry |
|-------------|----------|-------------------------------|
| CT101-1A | 1 | *User Defined |
| CT101-1B | 1 | **1/2" Conduit Fitting |
| CT101-1C | 1 | Cord Grips |
| CT101-2A | 2 | *User Defined |
| CT101-2B | 2 | **1/2" Conduit Fitting |
| CT101-2C | 2 | Cord Grips |
| CT101-3A | 3 | *User Defined |
| CT101-3B | 3 | **3/4" Conduit Fitting |
| CT101-3C | 3 | Cord Grips |
| CT101-4A | 4 | *User Defined |
| CT101-4B | 4 | **3/4" Conduit Fitting |
| CT101-4C | 4 | Cord Grips |

Supplied Accessories: **Mounting brackets.**

* No punch outs are provided in the enclosure for cable entry. User may install any fitting required.

** For use with EMT (thin wall conduit).

